



ECOTAP HOMEBOX Coiled Cord with pushbutton, without registration



Specifications

Start- and Stopprocedure	Pushbutton
Number of charging points:	1
Connection:	Flexible coil cord, expandable up to 4 metres available in type 1 or type 2
Value of connectivity:	From 1x16A to 3x32A
Power output:	0 up to 22 Kw
Protocol:	Modus 3
Positioning:	Not applied
Communications:	Not applied
Casing material:	Steel 2,2 mm
Standard Colour:	RAL 7011/RAL 9016
Treatment:	Anti corrosion treatment and features powder coating
Measurements casing (HxDxB):	530mm x 200mm x 220mm
Weight	12kg
Norms:	EMC-richtlijn 2014/30/EU - EN / IEC 60950-22/2017 EN / IEC61851-1/2017 - EN/IEC61851-22/2002 EN/IEC 62196-2/2017 - EN IEC 61000-6-2/2016 EN IEC 61000-6-3/2007 + A1/2011 EN / IEC 60335-1/2012 + A13/2017 EN/IEC 60364-4-41/2017
Water resistance:	IP54
Vandalism resistance:	IK10
Operating/ambient temperature:	-25° tot + 60°
Connection terminals:	16 mm ²
Wall mounting:	4x12mm Mounting holes in wall adapter plate
Warranty standard:	1 year

