



ECOTAP HOMEBOX Socket type 2 with pushbutton

Specifications

| | |
|--------------------------------|---|
| Start- and Stopprocedure | Push Button |
| Number of charging points: | 1 |
| Connection: | Socket type 2 |
| Value of connectivity: | From 1x16A to 3x32A |
| Power output: | 0 up to 22 Kw |
| Protocol: | Modus 3 |
| Positioning: | Not applied |
| Communications: | Not applied |
| Casing material: | Steel 2,2 mm |
| Standard Colour: | RAL 7011/RAL 9016 |
| Treatment: | Anti corrosion treatment and features powder coating |
| Measurements casing (HxDxB): | 530mm x 200mm x 220mm |
| Weight | 11kg |
| Norms: | EMC-richtlijn 2014/30/EU - EN / IEC 60950-22/2017 EN / IEC61851-1/2017 - EN/IEC61851-22/2002 EN/IEC 62196-2/2017 - EN IEC 61000-6-2/2016 EN IEC 61000-6-3/2007 + A1/2011 EN / IEC 60335-1/2012 + A13/2017 EN/IEC 60364-4-41/2017 |
| Water resistance: | IP54 |
| Vandalism resistance: | IK10 |
| Operating/ambient temperature: | -25° tot + 60° |
| Connection terminals: | 16 mm ² |
| Wall mounting: | 4x12mm Mounting holes in wall adapter plate |
| Warranty standard: | 1 year |
| | |
| | |
| | |
| | |

