



ECOTAP Charging Station DUO

Specifications

The start/stop procedure	Works by means of a charging card or App
Number of connections:	2
Connections:	Type 2
Connection value:	1 of 3 x 16A up to 63A.
Power supply:	230V / 400V 50Hz
Power output per socket:	0 up to 22 Kw
Residual current device:	AC = 30 mA, DC = 6 mA
Protocol:	Mode 3
Positioning:	GPS
Communications:	UMTS/GSM Modem/ Controller with RFID-reader
Casing material:	Steel 4 mm
Standard Colour:	RAL 6018/RAL 9016
Treatment:	Anti-corrosion treatment and powder coating
Measurements casing (HxDxB):	1400mm x 240mm x 200mm
Weight:	56kg
European Standards:	Low voltage directive 2014/35/EU EMC direction 2014/30/EU
Standards:	BS EN 61851-1 BS EN 61851-22
Operating/ambient temperature:	-25° to 60°
Water resistance:	IP54
Vandalism resistance	IK10
Warranty:	Standard: 1 year
(Optional: Warranty Plus + 4 years)	

This car charging station works on three-phase electric power and features car communication technology. It was specifically designed for public places prone to vandalism. Therefore this chargingstation is Vandalism resistant and is Made of 4 mm steel.

Smart Charging

Makes smart charging of electric cars accessible to everyone. Smart Charging means that the available power capacity is used in a "smart" fashion. The charging capacity is always optimally divided among the charging stations in use.



CONTACT

Telephone: +31 (0) 411 210 210
 Website: www.ecotap.nl
 Email: info@ecotap.nl

