



Specifications

The start/stop procedure	Works by means of a charging card
Number of connections:	2
Connections:	2 (7-PINS) sockets
Connection value:	1 of 3 x 16A up to 3 x 80A
Power supply:	230V / 400V 50Hz
Power output per socket:	0 up to 22 Kw
Protocol:	Mode 3
Positioning:	GPS
Communications:	UMTS/GSM Modem/ Controller with RFID-reader
Casing material:	Steel 4 mm/Scales: 3,6 mm
Standard Colour:	RAL 6018/RAL 9016
Treatment:	Anti-corrosion and powder coating
Measurements casing (HxDxB):	1400mm x 180mm x 360mm
Weight:	66,5kg
Norms:	NEN1010/EU/35-IEC: 61851-1 VDE-AR-E 2623-2-2
Water resistance: IP54	IP54
Vandalism resistance	IK10
Warranty:	standard 1 year
(Optional: Warranty Plus)	

ECOTAP Charging Station DUO Wide

It was specifically designed for public places prone to vandalism. Therefore this charging station is Vandalism resistant and is Made of 4 mm steel. By its shape this Charging Station is Suitable for networking connections.

2 cars can be charged at the same time.

Smart Charging

Makes smart charging of electric cars accessible to everyone. Smart Charging means that the available power capacity is used in a "smart" fashion. The charging capacity is always optimally divided among the charging stations in use.

